



DESCRIPTION

Sellotape® BG Tape consists of a stabilised, plasticised, soft PVC film coated with a rubber-based pressure sensitive adhesive. It has moisture resistance and anti-corrosive properties. BG Tape has outstanding conformability and adhesion to metal and plastic. The non-corrosive, pressure-sensitive adhesive removes the need for heat, moisture or other catalysts for application.

The physical and performance properties shown are averages obtained from tests recommended by ASTM D-1000. A particular roll may vary very slightly from these averages and it is recommended that the buyer determine the suitability for their own purposes.



APPLICATIONS

- Sealing the open end of pipes to avoid contamination.
- Joining silage wrap.
- Joining polythene strawberry covers.
- Joining polythene underlay prior to laying of concrete.
- Holding building paper in place.
- B.G Tape can be used for a wide variety of sealing jobs due to its conformability to irregular surfaces.
- Temporary holding applications.
- Suitable for sealing lids on drums or tins.
- As a hand grip for a variety of tools to prevent injury from rough surfaces.
- Repairing or mending of plastic products.
- Whenever you need strong dependable holding or reinforcing.
- Bundling and strapping applications.

SPECIFICATIONS

| BACKING | PVC |
|------------------|--------------------------|
| ADHESIVE | Rubber |
| TOTAL THICKNESS | 160 microns |
| ADHESION | 0.16 kg / cm (1.6N/10mm) |
| TENSILE STRENGTH | 2.6kg / cm (25.5N/10mm) |
| ELONGATION | 200% |
| COLOURS | Black, White |

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.